



New Product

285-13

DTM Urethane Primer - Dark Gray

Number: GLABUL0151-ES

Date: May, 2007

Glasurit® Brand Management is pleased to introduce 285-13 DTM Urethane Primer.

This new primer/surfacer has been designed for general refinish use in areas not regulated by low VOC requirements.

This product offers fast cure and early air-dry sanding. Baking or the use of IR lamps can improve curing even further.

Additional features include superior sprayability, relatively long usable potlife, easy sanding, and excellent topcoat holdout and repair appearance. Handling and spraying are very easy and predictable. In addition, this primer is very sag resistant.

Glasurit 285-13 is suitable for direct use over a wide assortment of common automotive substrates including galvanized, aluminum, steel, old paint, plastics, fiberglass, and SMC, without the need for an etching primer precoat (except for raw plastic parts). This primer can also be used over flexible substrates, if used in conjunction with Glasurit elastifier as recommended in our technical data sheets.

This new product is offered in a dark gray color, allowing for its use under dark topcoats, reducing the need to spend time and money tinting primers with expensive topcoat toner.

A Material Safety Data Sheet (MSDS) for this product may be viewed and downloaded from www.basrefinish.com/glasurit.html



Advantages

- Fast curing
- Superior sprayability
- Easy sanding
- Excellent topcoat holdout and repair appearance
- Sag resistant

Ratio

100 parts 285-13

25 parts 929-51 or 929-53

Additional Information

- BASF Part Number: 28513Z-7785
- UPC Code: 652282020483
- UN DOT Number: 1263
- Packing Group: II
- Can Dimension: 7.656"H x 6.6" Dia
- Units/Case: 4
- Case Dimension: 13¼"L x 13¼"W x 8"H
- Wt/Case: 50.4 lbs